

DMX Channel Index

impression[&]
S350 WASH



Fixture software version 48



GLP® impression® S350 Wash DMX Channel Index Revision A

This document covers fixture software version 48

© 2017-2019 German Light Products GmbH. All rights reserved.

The marks 'GLP' and 'German Light Products' are trademarks registered as the property of German Light Products GmbH in Germany, in the United States of America and in other countries.

The information contained in this document is subject to change without notice. German Light Products GmbH and all affiliated companies disclaim liability for any injury, damage, direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document.

Manufacturer's head office:

German Light Products GmbH (GLP), Industriestrasse 2, 76307 Karlsbad, Germany
Tel (Germany): +49 7248 92719 - 0

Service & Support EMEA:

GLP, Industriestrasse 2, 76307 Karlsbad, Germany
Tel. (Germany): +49 7248 9271955
Email: support@glp.de
www.glp.de

Service & Support USA:

GLP USA, 1145 Arroyo St., Ste. A, 91340 San Fernando, California
Tel (USA): +1 818 767 8899
Support (US): info@germanlightproducts.com
www.germanlightproducts.com

Impression S350 Wash DMX channel index

Normal Mode (27 DMX channels)

Channel	Function	Description	DMX range	Default DMX	% Range	Fade
1	Pan coarse	Left – right in 1.2° increments (16 bit)	0 – 65535	32767	0 – 100%	Fade
2	Pan fine					
3	Tilt coarse	Up – down in 1.2° increments (16 bit)	0 – 65535	32767	0 – 100%	Fade
4	Tilt fine					
5	Color wheel	Open – White 6000 K	0 – 3	0	0 – 1.2%	Snap
		Color 01 – Red	4 – 7		1.6 – 2.7%	Snap
		Color 02 – Green	8 – 11		3.1 – 4.3%	Snap
		Color 03 – CTO 2700 K	12 – 15		4.7 – 5.9%	Snap
		Color 04 – CTO 3200 K	16 – 19		6.3 – 7.5%	Snap
		Color 05 – CTO 4200 K	20 – 23		7.8 – 9.0%	Snap
		Color 06 – CTO 7500 K	24 – 27		9.4 – 10.6%	Snap
		Color 07 – Congo blue (UV)	28 – 31		11.0 – 12.2%	Snap
		Color 08 – Magenta	32 – 35		12.5 – 13.7%	Snap
		Color 09 – Orange	36 – 39		14.1 – 15.3%	Snap
Color 10 – Blue	40 – 43	15.7 – 16.9%	Snap			
	Color wheel indexing 0 – 360° (continuous color changing)	44 – 167	17.3 – 65.5%	Fade		
	Color wheel rotation					
	CW fast – slow	168 – 211	65.9 – 82.7%	Fade		
	Color wheel rotation stop	212	83.1%	Snap		
	Color wheel rotation					
	CCW slow – fast	213 – 255	83.5 – 100%	Fade		
6	Cyan	Cyan 0 – 100%	0 – 255	0	0 – 100%	Fade
7	Magenta	Magenta 0 – 100%	0 – 255	0	0 – 100%	Fade
8	Yellow	Yellow 0 – 100%	0 – 255	0	0 – 100%	Fade
9	CTC	Off (default: 6000 K)	0 – 31	0	0 – 12.2%	Snap
		8000 K	32 – 35		12.5 – 13.7%	Fade
		7900 K	36 – 39		14.1 – 15.3%	
		7800 K	40 – 43		15.7 – 16.9%	
		7700 K	44 – 47		17.3 – 18.4%	
		7600 K	48 – 51		18.8 – 20.0%	
		7500 K	52 – 55		20.4 – 21.6%	
		7400 K	56 – 59		22.0 – 23.1%	
		7300 K	60 – 63		23.5 – 24.7%	
		7200 K	64 – 67		25.1 – 26.3%	
		7100 K	68 – 71		26.7 – 27.8%	
		7000 K	72 – 75		28.2 – 29.4%	
		6900 K	76 – 79		29.8 – 31.0%	
		6800 K	80 – 83		31.4 – 32.5%	
		6700 K	84 – 87		32.9 – 34.1%	
		6600 K	88 – 91		34.5 – 35.7%	
		6500 K	92 – 95		36.1 – 37.3%	
		6400 K	96 – 99		37.6 – 38.8%	
		6300 K	100 – 103		39.2 – 40.4%	
		6200 K	104 – 107		40.8 – 42.0%	
6100 K	108 – 111	42.4 – 43.5%				
6000 K	112 – 115	43.9 – 45.1%				
5900 K	116 – 119	45.5 – 46.7%				

9 continued		5800 K	120 – 123		47.1 – 48.2%	Fade
		5700 K	124 – 127		48.6 – 49.8%	
		5600 K	128 – 131		50.2 – 51.4%	
		5500 K	132 – 135		51.8 – 52.9%	
		5400 K	136 – 139		53.3 – 54.5%	
		5300 K	140 – 143		54.9 – 56.1%	
		5200 K	144 – 147		56.5 – 57.6%	
		5100 K	148 – 151		58.0 – 59.2%	
		5000 K	152 – 155		59.6 – 60.8%	
		4900 K	156 – 159		61.2 – 62.4%	
		4800 K	160 – 163		62.7 – 63.9%	
		4700 K	164 – 167		64.3 – 65.5%	
		4600 K	168 – 171		65.9 – 67.1%	
		4500 K	172 – 175		67.5 – 68.6%	
		4400 K	176 – 179		69.0 – 70.2%	
		4300 K	180 – 183		70.6 – 71.8%	
		4200 K	184 – 187		72.2 – 73.3%	
		4100 K	188 – 191		73.7 – 74.9%	
		4000 K	192 – 195		75.3 – 76.5%	
		3900 K	196 – 199		76.9 – 78.0%	
		3800 K	200 – 203		78.4 – 79.6%	
		3700 K	204 – 207		80.0 – 81.2%	
		3600 K	208 – 211		81.6 – 82.7%	
		3500 K	212 – 215		83.1 – 84.3%	
		3400 K	216 – 219		84.7 – 85.9%	
		3300 K	220 – 223		86.3 – 87.5%	
		3200 K	224 – 227		87.8 – 89.0%	
	3100 K	228 – 231		89.4 – 90.6%		
	3000 K	232 – 235		91.0 – 92.2%		
	2900 K	236 – 239		92.5 – 93.7%		
	2800 K	240 – 243		94.1 – 95.3%		
	2700 K	244 – 247		95.7 – 96.9%		
	2600 K	248 – 251		97.3 – 98.4%		
	2500 K	252 – 255		98.8 – 100%		
10	Shutter	Closed	0 – 15	255	0 – 5.9%	Snap Fade
		Pulse, random, slow – fast	16 – 47		6.3 – 18.4%	
		Ramp-up, random, slow – fast	48 – 79		18.8 – 31%	
		Ramp-down, random, slow – fast	80 – 111		31.4 – 43.5%	
		Ramp-up-down, random, slow – fast	112 – 143		43.9 – 56.1%	
		Strobe with b/o pause 5 – 0.1 sec.	144 – 199		56.5 – 78.0%	
		Strobe 1 – 10 Hz	200 – 239		78.4 – 93.7%	
		Open	240 – 255		94.1 – 100%	Snap
11	Dimmer coarse	Intensity 0 – 100%	0 – 65535	32768	0 – 100%	Fade
12	Dimmer fine					
13	Focus	Near – far	0 – 255	128	0 – 100%	Fade
14	Zoom	Wide – narrow	0 – 255	127	0 – 100%	Fade

15	Framing module indexing	CW indexing from 0° to -45° Center: 0° CCW indexing from 0° to +45°	0 – 128 128 129 – 255	128	0 – 50.2% 50.2% 50.6 – 100%	Fade Snap Fade
16	Framing blade 1 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
17	Framing blade 1 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
18	Framing blade 2 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
19	Framing blade 2 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
20	Framing blade 3 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
21	Framing blade 3 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
22	Framing blade 4 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
23	Framing blade 4 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
24	Iris	Open → closed	0 – 255	0	0 – 100%	Fade
25	Special / Control	No function Performance fast* Performance normal* Performance smooth* Nu function Dimmer curve extra soft* Dimmer curve linear* No function Display off* Display auto-off* Display on* Display orientation normal* Display orientation invert* No function No DMX = blackout* No DMX = hold* No DMX = stand-alone* No DMX = DMX shot* No function Fan regulated* Fan high* Fan medium* Fan low* No function Position feedback off* Position feedback on* Effect shortcuts off* Effect shortcuts on* Tilt invert off* Tilt invert on* Pan invert off* Pan invert on* Zoom invert off* Zoom invert on*	0 – 26 27 – 29 30 – 32 33 – 35 36 – 38 39 – 41 42 – 44 45 – 53 54 – 56 57 – 59 60 – 62 63 – 65 66 – 68 69 – 71 72 – 74 75 – 77 78 – 80 81 – 83 84 – 86 87 – 89 90 – 92 93 – 95 96 – 98 99 – 104 105 – 107 108 – 110 111 – 113 114 – 116 117 – 119 120 – 122 123 – 125 126 – 128 129 – 131 132 – 134	0	0 – 10.2% 10.6 – 11.4% 11.8 – 12.5% 12.9 – 13.7% 14.1 – 14.9% 15.3 – 16.1% 16.5 – 17.3% 17.6 – 20.8% 21.2 – 22% 22.4 – 23.1% 23.5 – 24.3% 24.7 – 25.5% 25.9 – 26.7% 27.1 – 27.8% 28.2 – 29.0% 29.4 – 30.2% 30.6 – 31.4% 31.8 – 32.5% 32.9 – 33.7% 34.1 – 34.9% 35.3 – 36.1% 36.5 – 37.3% 37.6 – 38.4% 38.8 – 40.8% 41.2 – 42.0% 42.4 – 43.1% 43.5 – 44.3% 44.7 – 45.5% 45.9 – 46.7% 47.1 – 47.8% 48.2 – 49.0% 49.4 – 50.2% 50.6 – 51.4% 51.8 – 52.5%	Snap

25 (contd.)	Special/Control (contd.)	Focus tracking off*	141 – 143	0	55.3 – 56.1%	Snap
		Focus tracking near*	144 – 146		56.5 – 57.3%	
		Focus tracking medium*	147 – 149		57.6 – 58.4%	
		Focus tracking far*	150 – 152		58.8 – 59.6%	
		No function	153 – 158		60.0 – 62.0%	
		Framing Control = PI Mode (position/Index)*	159 – 161		62.4 – 63.1%	
		Framing Control = LR Mode (left/right)*	162 – 164		63.5 – 64.3%	
		No function	165 – 191		64.7 – 74.9%	
		PWM 2200 Hz **	192 – 194		75.3 – 76.1%	
		PWM 3000 Hz **	195 – 197		76.5 – 77.3%	
		PWM 4800 Hz **	198 – 200		77.6 – 78.4%	
		PWM 9600 Hz **	201 – 203		78.8 – 79.6%	
		No function	204 – 206		80.0 – 80.8%	
		PWM 25 kHz **	207 – 209		81.2 – 82.0%	
		Set fixture to factory defaults**	240 – 242		94.1 – 94.9%	
		No function	243 – 245		95.3 – 96.1%	
		Reset pan/tilt *	246 – 248		96.5 – 97.3%	
Reset head*	249 – 251	97.6 – 98.4%				
Reset all*	252 – 255	98.8 – 100%				
26	FX1 selection	No FX	0 – 10	0	0 – 3.9%	Snap
		LED cluster FX 01 Chaser	11 – 14		4.3 – 5.5%	
		LED cluster FX 01 Crossfade	15 – 18		5.9 – 7.1%	
		LED cluster FX 02 Chaser	19 – 22		7.5 – 8.6%	
		LED cluster FX 02 Crossfade	23 – 26		9 – 10.2%	
		LED cluster FX 03 Chaser	27 – 30		10.6 – 11.8%	
		LED cluster FX 03 Crossfade	31 – 34		12.2 – 13.3%	
		LED cluster FX 04 Chaser random	35 – 38		13.7 – 14.9%	
		LED cluster FX 04 Crossfade random	39 – 42		15.3 – 16.5%	
No function	43-255	16.9 – 100%				
27	FX1 adjustment	FX1 speed slow – fast	0 – 255	0	0 – 100%	Fade

* Move from zero and hold value for 3 seconds to apply

** Move from zero and hold value for 5 seconds to apply

Notes:

Percentage values are calculated by dividing DMX values by 2.56 and rounding to the nearest 0.1%.

To apply a command on Channel 25 (Special/Control), start at a value of zero, then move to the required value and hold it for the required time (e.g. 3 seconds). If you move to the required value from any other value than zero, the command will not be applied.

To adjust the PWM frequency using the Special/Control channel, start at a value of zero, move to the required value and hold it for at least 5 seconds.

Default settings are written in **bold type**.

